

	`		22	20	
					□ <u></u>
- · · · · · · · · · · · · · · · · · · ·					
	21		-0-0-		1 2
	,	73			
		╎			
127			可具具		38
	. ,				
maje symb W Born					
1200					\$ -
	1 : :				
less.					
				┦┙┖╬╂┥┸┙ ╴	- !
• • • •				bada	
:					
	: 1 : :1:	زجـا ا	3		
				(c . 1	· ·
· · ·				F1G. 1	
ø					


hrande en regini Mitalia Silika estant contente dell'in ent

-			22	124 1-162.		- 20
	<u> </u>			36	/ 20 ///// 8	
The state of the s				36	36 30	32
		////			34	
				F1G. 3		
-		c				





FIGS



F1G.6

Figure 1: Generic Vibration Criterion (VC) Curves for Vibration-Sensitive Equipment - Showing also the ISO Guidelines for People in Buildings (see Table 1 for description of equipment and uses)





FIG 7



F19.8



F19.9



Fig. 10

[NOTE: 1004 IS RESAR ON TOP OF COLUMN]





Fig. 11

[NOTE: 1102 IS SCARDLDWG]



F19.12







Fig. 13










NOTES:

- 1. CONCRETE COLUMN.
- 2. DOWELS TO MATCH AND LAP VERTICAL COLUMN REINFORCING PER G.S.N.
- 3. CONCRETE FOOTING,
- 4. CONCRETE CLOSURE POUR WHERE SHOWN ON PLAN. SEE TYPICAL DETAIL.
- 5. CONCRETE SLAB ON GRADE.





NO SCALE





THITERIOR CONCRETE COLUMN FOOTING


NO SCALE


NOTES.


STEEL ANGLE 4" X 4" X 3/8"











C.I.P. CONCRETE COLUMN WITH CONCRETE WAFFLE SLAB

